

Angular Contact Bearing Swivels

Product information




- YOKE Swivels are manufactured using the highest grade of material available.
- YOKE Swivels are available in sizes from 3/4 tonnes to 25 tonnes.
- YOKE Swivels are available for wire lines 1/4" to 1-1/2".
- YOKE Swivels are zinc plated for corrosion resistance and longer life.
- YOKE Swivels are manufactured with grease fittings for superior performance.
- YOKE Swivels are designed for low starting torque and high rotation speed.
- All Swivels parts are 100% magnaflux crack detected.
- 20,000 cycle fatigue rate to 1.5 times working load limit.
- All parts with batch number for quality certified and traceability.
- Minimum Ultimate Load is 5 times the Working Load Limit. Maximum Proof Load is 2 times the Working Load Limit.

... [Read more](#)

Safety factor: 5:1

Angular Contact Bearing Swivels

Blueprint



Technical data

Part Code	WLL ton	A mm	B mm	C mm	D mm	H mm	K mm	L mm	Weight (kg)
422500080500	0.75	15	32	12	10	22	103	126	0.5
422500100500	1	18	40	16	11	26	112	144	0.8
422500300500	3	23	51	23	16	31	159	203	2
422500500500	5	32	64	31	22	37	200	262	4
422500850500	8.5	37	76	35	25	50	242	312	6.7
422501000500	10	42	102	46	38	53	317	408	18.2
422501500500	15	48	108	46	38	56	317	408	21
422502500500	25	62	132	61	51	69	374	495	36.5