

Industrial Lever Block AL-3

Product information



L-3 series lever blocks are used for general hoisting in the mining, construction, industrial and domestic situations. Commonly used for short lifts and pulling applications.

Standard height of lift 1.5 or 3M except for 250kg which has 1 metre lift. Other lift height available upon request.


Features:

- Robust, durable, portable and compact in construction.
- All lever blocks come with ball bearing swivel hook.

[... Read more](#)

Industrial Lever Block AL-3

Blueprint



Technical data

Part Code	WLL ton	Lifting height m	Number of falls	A mm	B mm	C mm	D mm	Weight (kg)
500500030100780	0.25	1	1	92	75	205	153	0.38
500500050300780	0.5	3	1	110	82	260	251	3.5
500500050150784	0.5	1.5	1	110	82	260	251	3.5
500500080150780	0.8	1.5	1	152	128	295	256	7
500500080300780	0.8	3	1	152	128	295	256	7
500500080600780	0.8	6	1	152	128	295	256	7
500500100150780	1	1.5	1	152	128	295	256	7.2
500500100300780	1	3	1	152	128	295	256	7.2
500500160300780	1.6	3	1	175	148	335	368	11
500500160150784	1.6	1.5	1	175	148	335	368	11
500500320300780	3.2	3	1	195	181	450	368	20
500500320150784	3.2	1.5	1	195	181	450	368	20
500500630300780	6.3	3	2	195	232	542	368	28
500500630150784	6.3	1.5	2	195	232	542	368	28
500500630600780	6.3	6	2	195	132	542	368	28
500500900300780	9	3	3	366	195	645	368	43