

HXW/HSXW horizontal lifting clamps

Product information




General: For horizontal lifting and moving of steel plates. Clamp with compact shape and relative light unit weight. HXW/HSXW pewag winner lifting clamps **must always be used in pairs (or multiples thereof)**. Lifting capacity and jaw opening are clearly engraved in the body. The Working Load Limits indicated are per pair of lifting clamps. The HSXW clamps have a larger jaw opening.

... [Read more](#)

Note: The given WLL is valid per pair.

HXW/HSXW horizontal lifting clamps

Blueprint



Technical data

Part Code	Code	WLL ton	Jaw width mm	H mm	S mm	T mm	U mm	V mm	W mm	X mm	Y mm	Weight (kg)
502100100350490	HXW 1 t	1	0-35	11.5	99	25	188	140	10	65	15	2.6
502100200600490	HXW 2 t	2	0-60	19.5	118	30.5	287	180	15	90	16	7
502100201000490	HSXW 2 t	2	0-100	19.5	120	30.5	383	180	15	90	15	9.2
502100300600490	HXW 3 t	3	0-60	19.5	118	30.5	291	180	20	90	16	8
502100301000490	HSXW 3 t	3	0-100	19.5	120	30.5	387	180	20	90	15	10
502100400600490	HXW 4 t	4	0-60	19.5	145	30.5	304	220	25	105	20	13
502100401000490	HSXW 4 t	4	0-100	19.5	145	30.5	414	220	25	105	20	15
502100600600490	HXW 6 t	6	0-60	19.5	145	30.5	307	220	25	110	20	14
502100601000490	HSXW 6 t	6	0-100	19.5	145	30.5	414	220	25	120	20	16.5
502100800600490	HXW 8 t	8	0-60	19.5	135	30.5	336	225	35	120	30	19
502100801000490	HSXW 8 t	8	0-100	19.5	135	30.5	428	225	35	120	30	21
502101000600490	HXW 10 t	10	0-60	19.5	135	30.5	336	225	35	120	30	19
502101001000490	HSXW 10 t	10	0-100	19.5	135	30.5	428	225	35	120	30	22
502101200600490	HXW 12 t	12	0-60	19.5	135	30.5	336	225	35	120	30	19
502101201000490	HSXW 12 t	12	0-100	19.5	135	30.5	428	225	35	120	30	22
502101500600490	HXW 15 t	15	0-60	21.5	147	43	344	262	35	160	35	30
502101501500490	HSXW 15 t	15	0-150	27.5	240	45	665	350	35	140	35	53
502102500600490	HXW 25 t	25	0-60	21.5	147	43	349	262	40	175	35	33