

Beam Clamp WH UBC Universal

Product information



The William Hackett Universal Beam Clamp has been designed for vertical use, and side load applications, where conventional clamps are not. The Universal Beam Clamp is suitable for pulling and lifting at angles across the beam or as a semi-permanent anchor point. It can be loaded at any angle and eliminates the use of spreader beams in various lifting operations.

Fitted with an adjustable locking mechanism, ensuring secure clamping to the beam. Built-in suspension point for low headroom design.

Lightweight design allowing for quick clamping and unclamping. Our 10.0 tonne extra wide clamp is designed to accommodate a range of beam widths and thicknesses.

... [Read more](#)


Marking: According to standard

Standard: EN 13155

AS 4991

Beam Clamp WH UBC Universal

Blueprint



Technical data

Part Code	WLL ton	Beam width mm	A mm	B mm	C mm	D mm	E mm	F mm	G mm
502300202040500	2	76-204	450	203	22.5	Ø58	32.5	118	16
502300322040500	3.2	125-204	550	235	28	Ø60	33	133	20
502300503050500	5	125-305	618.5	270	37.5	Ø75	36	157	24
502301003050500	10	125-305	618.5	270	35	Ø80	36	225	44
502301004050500	10	225-405	700	298	38	Ø80	70	230	44