

Chain SA/S - EN818-2 Gr. 10

Product information



General: Chain for lifting or lashing (other safety factor). Available in 2 different qualities

Star Alloy (SA/S)

- Working temperature: max. 200°C
- Grade Marking: "10" on link every 300mm (up to 16mm) others every 900 mm.
- Surface: Purple varnished

Star Alloy Plus+ (SAP/S): for working temperatures up to 380°C (Available on request)

... [Read more](#)

Material: Alloy steel.

Marking: According to standard

Temperature range: Star Alloy SA/S: -40°C up to 200°C - Star Alloy Plus+ SAP/S: -40°C up to 380°C

Standard: EN 818-2

higher capacity

Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

Chain SA/S - EN818-2 Gr. 10

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	Min. breaking force kN	Pitch Length	D mm	P mm	Li min. mm	Le max. mm	Weight kg/m
2035006000000050	6	1.4	56.5	18	6	18	8.7	22	0.96
2035007000000050	7	1.9	77	21	7	21	9.5	25	1.2
2035008000000050	8	2.5	101	24	8	24	10.9	29	1.57
2035010000000050	10	4	157	30	10	30	13.5	36	2.46
2035013000000050	13	6.7	265	39	13	39	17.5	47	4.18
2035016000000050	16	10	402	48	16	48	21.5	58	6.28
2035019000000050	19	14	567	57	19	57	26.6	69	8.9
2035022000000050	22	19	760	66	22	66	29.5	79	11.88
2035026000000050	26	26.5	1,060	78	26	78	35	94	16.18
2035020000000050	20	-	-	60	-	-	-	-	-