Lifting Solutions Group
Axel Johnson International

Ferrule UM Talurit®

Product information



The turnback ferrule system is easy to use. It is quick, safe and has proved itself to be totally reliable. The ferrules are thoroughly specified and very well defined for many different wire rope applications.

The ferrules can be used for single layer steel wire ropes with round strands up to fill factor 0,60 and grade 1960.

... *Read more*

Material: Aluminum
Marking: According to standard
Standard: EN 13411-3
except rope type range
Note: See the manufacturer's product data sheet below for guidance on dimension selection.

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Ferrule UM Talurit®

Technical data

Part Code	Ferrule size mm	Length mm
120100900120	9	36
120101000120	10	41
120101100120	11	45
120101200120	12	50
120101300120	13	55
120101400120	14	59
120101600120	16	64
120101800120	18	73
120102000120	20	82
120102200120	22	91
120102400120	24	100
120102600120	26	109
120102800120	28	118
120103000120	30	127
120103200120	32	136
120103400120	34	146
120103600120	36	155
120103800120	38	164
120104000120	40	173
120104200120	42	182
120104400120	44	191
120104600120	46	200
120105000120	50	209
120105400120	54	228
120105800120	58	246
120106200120	62	264
120106600120	66	282
120107000120	70	300
120107400120	74	319
120107800120	78	337
120108200120	82	355

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Ferrule UM Talurit®

Technical data

Part Code	Ferrule size mm	Length mm
120109000120	90	391

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved