Lifting Solutions Group
Axel Johnson International

Grab Hook Pewag PSW with Safety Catch

Product information



This standard shortening hook ensures optimal interaction between chain and hook thanks to the special design of the chain contact area. Moreover, the integrated safety catch protects the chain from an accidental release. Tip loading is not allowed as well as the assembling with Unilock connection links. Further, the usage in the welded system has to be prevented.
Even when shortened, the load capacity is not reduced.

... *Read more*

Material: High duty grade 10.
Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.
Temperature range: -40ºC up to +380°C.
Finish: Orange powder coated.
Standard: EN 1677-1

Safety factor: 4:1
Grade: 10


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Grab Hook Pewag PSW with Safety Catch

Blueprint



Technical data

Part Code	Code	WLL ton	LC kN	EWL mm	b mm	d1 mm	d2 mm	e mm	g mm	Weight (kg)
402300250510	PSW 7/8	2.5	50	65	57	16	12	65	9	0.37
402300400510	PSW 10	4	80	77	71	20	14	77	12	0.7
402300670510	PSW 13	6.7	134	101	92	26	19	101	15	1.56
402301000510	PSW 16	10	200	121	113	32	23	121	19	2.9

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved