Lifting Solutions Group
Axel Johnson International

# Lifting Point Pewag PLEW

**Product information**




Lifting point for welding onto machine parts or vehicle bodies. Ideal for hanging of lifting and lashing parts. Due to the integreated spring, the ring will be kept in each requested position.
The instructions according to DIN EN ISO 14341 are valid for the welding.
The welding may only be carried out by a welding operator with a valid qualification according to EN 287-1 or EN ISO 9606-1.
The lifting points will be packed individually and together with a user manual and welding instructions.

**Permissible usage**
Load capacity acc. to the inspection certificate respectively table of WLL in the mentioned directions of pull (see picture 1 and 2).

**Non permissible usage**
Make sure when choosing the assembly that improper load can not arise e.g. if:

- The direction of pull is obstructed
- Direction of pull is not in the foreseen area
- Loading ring rests against edges and load

... *Read more*

**Material:** Alloy steel
**Marking:** CE-marked, WLL and the load capacity is clearly marked on the welding pad

**Safety factor:** 4:1


**Certex Lifting**
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Lifting Point Pewag PLEW

## Blueprint




## Technical data

| Part Code | Code | WLL ton | a mm | b mm | c mm | d mm | e mm | f mm | h mm | l mm | Weight (kg) |
|---|---|---|---|---|---|---|---|---|---|---|---|
| 42154013879 | PLEW 1,5 t | 1.5 | 32 | 38 | 65 | 14 | 65 | 40 | 25 | 35 | 0.32 |
| 42154013891 | PLEW 2,5 t | 2.5 | 37 | 44 | 75 | 16 | 76 | 47 | 28 | 41 | 0.5 |
| 42154011912 | PLEW 4 t | 4 | 43 | 48 | 84 | 18 | 83 | 51 | 32 | 45 | 0.75 |
| 42154013895 | PLEW 6,7 t | 6.7 | 58 | 60 | 107 | 24 | 108 | 64 | 44 | 56 | 1.7 |
| 42154013883 | PLEW 10 t | 10 | 69 | 66 | 126 | 27 | 123 | 69 | 54 | 61 | 2.8 |
| 42154013887 | PLEW 19 t | 19 | 92 | 95 | 171 | 38 | 168 | 100 | 68 | 89 | 6.5 |


© November 2026 - All Rights Reserved