Lifting Solutions Group
Axel Johnson International

Master Link HA® Quad Assembly OS+

Product information

The HA range of links are widely used in lifting sets for offshore containers.

... *Read more*

Material: Triple Alloy Steel
Marking: According to standard
Temperature range: -40°C up to 200°C
Standard: EN 1677-4
AS 3776

Safety factor: 5:1
Grade: 8

© September 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Master Link HA® Quad Assembly OS+

Blueprint



Technical data

Part Code	Code	WLL ton	Min. breaking force kN	A mm	B mm	C mm	D mm	E mm	F mm	Weight (kg)
401100410630	HA16QA 8 OS+	4.1	101	16	150	75	14.5	125	60	1.62
401101450630	HA26QA 8 OS+	14.5	356	28	270	140	22	162	90	6.73
401103050630	HA40QA 8 OS+	30.5	749	40	280	155	32	270	140	18.5
401107500630	HA65QA 8 OS+	75	1,840	65	410	220	50	350	195	66.1
401110000630	HA75QA 8 OS+	100	2,453	75	450	250	65	410	220	115.02
401115000630	HA90QA	150	3,679	90	510	300	70	400	200	196.5

© September 2026 - All Rights Reserved