

Master Link Pewag MW Enlarged

Product information



MW Enlarged master links are designed for the assembly of chain slings. Can also be attached to wire rope slings. For pewag connex and welded system.

Master link SAW: Without flattened part for transition link and special colour ... [Read more](#)

Material: High duty grade 10.

Marking: According to standard, CE-marked, Pewag or PW, winner or 10, H16, batch code and type.

Temperature range: -40°C up to +380°C.

Finish: Orange powder coated.


Standard: EN 1677-4
AS 3776

Safety factor: 4:1

Grade: 10

Master Link Pewag MW Enlarged

Blueprint



Technical data

Part Code	Code	WLL ton	EWL	For chain mm, 1- leg	For chain mm, 2- leg	Use for hook DIN 15401 Nr	Double hook DIN 15402 no.	d mm	s mm	t mm	w mm mm	Weight (kg)
402100140300	MW 10	1.4	90	5	5	2,5	4	11	10	90	65	0.22
402100230300	MW 13	2.3	120	6+7	6	4	5	14	10	120	70	0.44
402100320300	MW 16	3.2	140	8	7	5	6	16	13	140	80	0.71
402100420300	MW 18	4.2	160	10	8	6	8	18	14	160	95	1.09
402100670300	MW 22	6.7	170	13	10	10	12	23	17	170	105	1.74
402101010300	MW 26	10.1	190	16	13	10	12	27	20	190	110	2.65
402101600300	MW 32	16	230	19	16	12	16	33	26	230	130	4.78
402102120300	MW 36	21.2	275	22	19	20	25	38	29	275	150	7.48
402104000300	MW 56	40	350	32	26	50	63	56	46	350	250	21.98