



Chain Block POWERTEX PCB-S2OLP with Ball Bearing Hook

Product information

The Powertex PCB-S2 OLP Chain Hoist is a high-quality chain block with a ball-bearing hook, designed to provide durability, safety, and ease of operation. With its ergonomic hand chain, advanced features, and built-in overload protection, this chain hoist ensures smooth and efficient lifting for various industrial applications. This OLP version has an integrated Overload Protection, which ensures safe lifting and prevents unintended overloading of the hoist.

Product benefits:

- **Overload protection device:** the OLP hoists are factory-equipped with an Overload Protection device, which limits the maximum operating force that can be applied using the hand chain, ensuring safe and controlled lifting operations.
- **Enhanced safety:** each hoist undergoes dynamic proof load testing at 1.5 times the Working Load Limit (WLL) before leaving the factory, ensuring maximum safety and reliability. The hoist is equipped with a well-covered automatic load reaction brake and features double safety with two brake pawls and four brake springs, exceeding EN 13157 and AS 1418.2 requirements. The load chain is calibrated, proof load tested and meets the requirements of EN 818-7.
- **Smooth and efficient operation:** the compact and lightweight construction, combined with a sprocket wheel equipped with needle bearings and a drive shaft supported by needle and slide bearings, ensures smooth and efficient operation. The fine-calibrated load chain offers quiet and seamless performance.
- **Quality load chain:** the load chain complies with the EN818-7 T(8) standard and features a Chrome 6-free electro-galvanized surface finish to protect it from corrosion.
- **Easy positioning and safe hooks:** swivel hooks at both ends make in-line positioning easy. The hooks are designed to open at overload instead of breaking, enhancing safety. Heavy-duty steel safety latches and deformation check dots forged into the side of the hooks allow for easy overload detection.
- **Convenient maintenance and documentation:** each hoist is RFID-equipped for easy service and inspection, and a QR code provides on-site access to multilingual user manuals. A test certificate and Declaration of Conformity are enclosed with each hoist, ensuring compliance and traceability.
- **Available spare parts:** spare parts such as hooks, brake discs, safety latches, and chains are readily available, ensuring that maintenance and repairs can be carried out efficiently and further extending the hoist's service life.

Product options:

- **Chain bag:** an optional chain bag is available for added convenience and organization.

Material: Durable all steel construction

Marking: According to standard, CE-marked, UKCA-marked, POWERTEX, Model, WLL, Chain, Serial number, User manual/QR code

Temperature range: -10°C up to +50°C

Finish: Red powder coated body and plated frame components

Standard: AS 1418.2, EN 13157, EN 818-7

Safety factor: 4:1

Part Code	WLL ton	Lifting height m	Number of falls	Model	Load chain mm	Hand chain mm	Hand force max. kg	A mm	B mm	C mm	D mm	H min mm	Weight (kg)
500100050300811	0.5	3	1	PCB-S2OLP/500KG PHCA BB	5,0 x 15,0	5,0 x 23,7	24.9	130	128	22	34	280	9.8
500100100300811	1	3	1	PCB-S2OLP/1000KG PHCA BB	6,3 x 19,0	5,0 x 23,7	28.4	150	145	26	39	330	11.7
500100200300811	2	3	1	PCB-S2OLP/2000KG PHCA BB	8,0 x 24,0	5,0 x 23,7	34.3	185	175	35	49	385	18.9
500100300300811	3	3	2	PCB-S2OLP/3000KG PHCA BB	7,1 x 21,0	5,0 x 23,7	34.3	220	158	37	50	510	28.9
500100500300811	5	3	2	PCB-S2OLP/5000KG PHCA BB	9,0 x 27,0	5,0 x 23,7	37.2	255	183	43	60	615	37.1
500100750300811	7.5	3	3	PCB-S2OLP/7500KG PHCA BB	9,0 x 27,0	5,0 x 23,7	36.8	430	189	47	67	690	50
500101000300811	10	3	4	PCB-S2OLP/10000KG PHCA BB	9,0 x 27,0	5,0 x 23,7	40	360	183	47	65	820	92.8

Blueprint

