



# Height Safety Anchor Point GEOMET

## Product information

Townley's GEOMET Height Safety Anchor Point is a robust fall protection anchor point, precision-engineered for both safety and performance. Constructed from high-tensile alloy steel, it delivers exceptional durability and reliability. With a rated capacity of 1–2 persons (21kN), it is designed to provide secure attachment points for various height safety systems.

This anchor point is available in both long and short series bolt options. It is designed to meet exacting safety requirements, making it the ideal choice for professionals working at heights.

Compliance Plates are also available on request.

### Features:

- Rated Capacity: 1 – 2 Persons
- Long and short series bolt options
- Non-removable bolt
- 100% Crack Detection
- Made in Australia

### Load Ring:

- Rated Capacity: 1 - 2 Persons
- Alloy steel construction
- Long and short series bolt options
- Non-removable bolt
- 100% Crack Detection
- Made in Australia
- AS/NZS 5532:2013

Product Code	A	B (mm)	C (mm)	D (mm)	E (mm)	G (mm)	K (mm)	L (mm)	N (mm)	Weight (kg)
FP-G-TSEB16	M16	50	39	16	55	16	75	30	10	0.4
FP-G-TSEBLS16	M16	50	39	16	55	16	75	180	10	0.6
FP-G-TSEB20	M20	50	39	16	55	16	75	30	12	0.6
FP-G-TSEBLS20	M20	50	39	16	55	16	75	180	12	0.8

### Important

All persons using this equipment must read and understand all instructions outlined in this document. Failure to do so may result in serious injury or death. Only to be used by competent persons who can provide proof of competency training by a registered training organisation. Training shall be in accordance with the relevant Australian standards that govern industrial fall arrest systems and devices.

**Material:** Alloy steel

**Marking:** According to standard

**Standard:** AS/NZS 5532

Part Code	Max. number of persons	Length mm	Thread	A mm	B mm	C mm	D mm	E mm	G mm	K mm	L mm	N mm	Weight (kg)
8415FPGTSEB16	2	30	M16	M16	50	39	16	55	16	75	30	10	0.4
8415FPGTSEB20	2	30	M20	M20	50	39	16	55	16	75	30	12	0.6
8415FPGTSEBLS16	2	180	M16	M16	50	39	16	55	16	75	180	10	0.6
8415FPGTSEBLS20	2	180	M20	M20	50	39	16	55	16	75	180	12	0.8

Blueprint

