Lifting Solutions Group
Axel Johnson International

Lifting Round Slings

Product information



Slings are fabricated using 100% high-tenacity polyester yarn and wound in a continuous hank to form an endless sling. Durable and specially woven, 100% polyester non-load bearing tubular sleeve to give maximum wear protection to the yarn hank.
Conforms to Australian Standard AS 4497.1.

Features:

- Each sling is proof tested 2 x WLL.
- Individually serial numbered.
- Supplied with individual test certificate.
- Break Load Limit is 7 x the load indicated
- Label is under a protective sleeve, to prevent damage to it.

... *Read more*

Material: Polyester
Marking: According to standard, Individually serial numbered.
Standard: AS 4497.1
Note: Black colour available upon request.

Safety factor: 7:1

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lifting Round Slings

Technical data

Part Code	WLL ton	EWL m	Weight (kg)
340100300450410	3	4.5	2.85
340100400050410	4	0.5	0.44
340100400350410	4	3.5	2.89
340100501000410	5	10	11
340100600250410	6	2.5	3.5
340101200300410	12	3	6.34
340101200600412	12	6	12.68
340102000500410	20	5	22.75
340102500300410	25	3	18.1
340102501000410	25	10	59.3
340103000350410	30	3.5	33
340103001200410	30	12	94.5
340106000800410	60	8	-

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved