Lifting Solutions Group
Axel Johnson International

# Geared Trolley TSG KITO

## Product information

**General:** Geared trolley with capacity from 0,125 tons up to 5 tons. The standard trolley includes rubber bumper, safety lug and suspender.

... *Read more*



**Material:** Pressed steel plate.
**Marking:** According to standard, CE-marked
**Temperature range:** -40°C up to +60°C (–20°C up to + 40°C for the use with a electric chain hoist)
**Standard:** EN 13157

**Safety factor:** 4:1

**Certex Lifting**
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

# Geared Trolley TSG KITO

## Technical data

| Part Code | WLL ton | Beam width mm | Model | Chain length m |
|---|---|---|---|---|
| 502600011630030 | 0.125 | 58-163 | Standard | 3 |
| 502600013050030 | 0.125 | 164-305 | W30 | 3 |
| 502600031630030 | 0.25 | 58-163 | Standard | 3 |
| 502600033050030 | 0.25 | 164-305 | W30 | 3 |
| 502600051630030 | 0.5 | 58-163 | Standard | 3 |
| 502600053050030 | 0.5 | 164-305 | W30 | 3 |
| 502600101630030 | 1 | 58-163 | Standard | 3 |
| 502600103050030 | 1 | 164-305 | W30 | 3 |
| 502600152040030 | 1.5 | 82-204 | Standard | 3 |
| 502600153050030 | 1.5 | 205-305 | W30 | 3 |
| 502600202040030 | 2 | 82-204 | Standard | 3 |
| 502600203050030 | 2 | 205-305 | W30 | 3 |
| 502600252040030 | 2.5 | 82-204 | Standard | 3 |
| 502600253050030 | 2.5 | 205-305 | W30 | 3 |
| 502600302040030 | 3 | 82-204 | Standard | 3 |
| 502600303050030 | 3 | 205-305 | W30 | 3 |
| 502600301530030 | 3 | 82-153 | - | 2.5 |
| 502600502040030 | 5 | 100-204 | Standard | 3.5 |
| 502600503050030 | 5 | 205-305 | W30 | 3,5 |
| 502600752200030 | 7.5 | 150-220 | Standard | 3.5 |
| 502600753050030 | 7.5 | 221-305 | W30 | 3,5 |
| 502601002200030 | 10 | 150-220 | Standard | 4 |
| 502601003050030 | 10 | 221-305 | W30 | 4,0 |
| 502601502200030 | 15 | 150-220 | Standard | 4.5 |
| 502601503050030 | 15 | 221-305 | W30 | 4.5 |
| 502602002200030 | 20 | 150-220 | Standard | 4.5 |
| 502602003050030 | 20 | 221-305 | W30 | 4.5 |
| 502603001900030 | 30 | 190 | Standard | 4.5 |
| 502603003050030 | 30 | 191-305 | W30 | 4.5 |

**Certex Lifting**
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved