Lifting Solutions Group
Axel Johnson International

Stubby Eye Bolt

Product information



Swivel Eye Bolt Points are accordingly to AS2318 for the swivel component. Used as a swiveling load ring able to swivel 360° with a pivot of 90°. Made from G100 alloy steel with Orange painted finish, manufactured with an elongated ring in metric thread sizes 8mm to 20mm

... *Read more*

Marking: WLL, size, quality mark and supplier identification


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Stubby Eye Bolt

Blueprint



Technical data

Part Code	WLL ton	Thread	A mm	B mm	C mm	D mm	E mm	F mm	Weight (kg)
4215605008	0.3	M8	38	26	45.3	11.5	25	8	0.11
4215605010	0.4	M10	38	26	45.3	14	25	8	0.12
4215605012	0.75	M12	43.5	32	54	17	33	10	0.2
4215605016	1.5	M16	52	37.5	63.5	24	36	14	0.35
4215605020	2.3	M20	63	44.5	78.5	30	47.5	20.6	0.66
4215605024	3.2	M24	74	51.6	92	35.5	53	20	1.1
4215605030	4.5	M30	92	65	118	45	68	24	2.07

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved