Lifting Solutions Group
Axel Johnson International

Replacement Links Crosby G-335 "Missing Link"®

Product information



Integral rivets join the two halves. After making connections, rivets must be peened.

Features:

- All sizes have countersunk rivet holes.
- Not suitable for use with Grade 80 or Grade 100 chain and chain slings used in overhead lifting.

... *Read more*

Material: Forged Steel, Quenched and Tempered

Safety factor: 4:1

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Replacement Links Crosby G-335 "Missing Link"®

Blueprint



Technical data

Part Code	Chain size mm	WLL ton	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight kg/100pc
40981013110	7	0.6	7.1	22.4	11.2	11.2	38.1	25.4	7.85	2.83
40981013156	10	1.25	10.4	28.7	14.2	14.2	52.5	35.1	11.9	9.07
40981013174	11	1.65	11.9	32.5	15	15	59.5	38.9	13.5	12.5
40981013192	13	2.15	13.5	37.3	16.8	16.8	67.5	43.7	15	17
40981013236	16	3.3	16.8	46	19.8	20.6	84	53	19.1	32.9
40981013254	19	4.65	19.8	54	23.9	26.9	98.5	63.5	22.4	55.5
40981013272	22	5.45	23.1	63.5	28.7	28.7	114	74.5	25.4	79.5
40981013290	26	7	26.2	70	31.8	31.8	127	84	28.7	113

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved