Lifting Solutions Group
Axel Johnson International

Welded Master Link Crosby A-347

Product information



Master link with large inner diameter and length.
These rings with auxiliaries have the dimensions that allow the manufacture of steel wire ropes slings with 3 or 4 legs.

... *Read more*

Material: Alloy steel — Quenched & Tempered
Marking: According to standard, Manufacturers name, traceability code.
Standard: EN 1677-4
AS 3776

Safety factor: 5:1
Grade: 8


Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Welded Master Link Crosby A-347

Blueprint



Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Welded Master Link Crosby A-347

Technical data

Part Code	Chain size mm	WLL ton	Chain Ø inch	Chain G80 3 and 4 legs	Chain G100 3 and 4 legs	A mm	B mm	C mm	D mm	E mm	F mm	G mm	Weight (kg)
401100240150	12-13	2.4	1/2	-	-	13	60	120	12	85	45	6.5	0.81
401100320150	13	3.2	-	6	6	13	60	120	13	120	60	6.5	1.1
401100410150	13-17	4.1	11/16	6-7	6	17	90	160	13	120	60	6.5	1.6
401100420150	13-19	4.2	3/4	7	6-7	19	90	160	13	120	60	6.5	1.8
401100580150	16-22	5.8	7/8	-	-	22	145	275	16	120	60	8.5	3.53
401100670150	17-22	6.7	7/8	-	-	22	100	180	17	160	90	8.5	3.35
401100700150	17-22	7	-	10	8	22	100	180	17	160	90	8.5	3.3
401100700151	17-22	7	-	10	8	22	145	275	17	160	90	8.5	4.1
401100850151	19-22	8.5	-	10	10	22	100	180	19	160	90	8.5	3.8
401100850150	20-22	8.5	7/8	-	-	22	90	170	20	150	80	8.5	3.93
401100890151	19-25	8.9	-	10	10	25	115	210	19	160	90	8.5	4.6
401100890150	19-25	8.9	1	10	10	25	145	275	19	160	90	8.5	5.3
401101070150	20-25	10.7	1	-	-	25	100	190	20	150	80	8.5	4.65
401101290150	22-28	12.9	1-1/8	-	-	28	110	210	22	170	90	10.5	6.4
401101450150	22-28	14.5	1-1/8	13	13	28	145	275	22	180	100	10.5	7.2
401101700150	25-31	17	1-7/32	16	13	32	145	275	25	210	115	13.5	9.9
401101700151	25-32	17	1-1/4	-	-	32	140	270	25	190	100	13.5	9.92
401102360150	28-36	23.6	-	16	16	36	155	285	28	190	110	13.5	12.7
401102810150	32-38	28.1	1-1/2	-	-	38	140	270	32	270	140	16.7	18.23
401102810152	32-40	28.1	-	19-20	16	40	140	270	32	275	145	16.7	18.4
401102810151	31-40	28.1	1-9/16	-	-	40	160	300	31	275	145	16.7	18.68
401103830150	36-45	38.3	1-3/4	22	19-20	45	180	340	36	285	155	-	26.7
401103830151	38-45	38.3	1-3/4	-	-	45	170	320	38	270	140	-	27.96
401104500150	38-50	45	2	-	-	50	200	380	38	270	140	-	32.86
401104500151	40-51	45	-	26	22-23	51	215	390	40	270	140	-	35.5
401104500150	45-51	45	2	-	-	51	190	350	45	340	180	-	42.92
401106700150	50-57	67	2-1/4	-	-	57	203	406	50	380	200	-	59.7
401106700151	51-55	67	-	32	26	55	203	406	51	390	215	-	61.1

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved