Lifting Solutions Group
Axel Johnson International

Lever Hoist WH L4

Product information



The design and specification of the William Hackett WH-L4 lever hoist includes:

WORKING LOAD LIMIT RANGE: 800kg to 20 tonnes.

LIGHT LOAD CAPABILITY: the WH L4 is tested and certified at 2% of the lever hoist rated capacity.

TWIN PAWL: double safety; fitted as standard.

SAFETY LATCHES: the WH L4 lever hoist top and bottom hooks are fitted with heavy duty cast steel latches. The latch and hook tips are integrated creating a strong and robust hook closure.

OVERLOAD INDICATOR MARKS: the WH L4 lever hoist

TOP AND BOTTOM HOOKS have, as part of the hook forging, overload indicator marks either side of the hook throat. By measuring the distance between the indicator marks, the hook can be quickly and easily checked to see if any stretch has occurred due to misuse or overloading.

HOOK HOUSING: the WH L4 lever hoist top and bottom hook housings are secured with socket head cap screws/hex head bolts and nyloc locking nuts.

FLEETING/CROSS HAULING: the WH L4 lever hoists are tested and certified for fleeting or cross hauling applications up to 45° from the vertical without deration.

LOAD CHAIN: the WH L4 lever hoists are fitted with load chain that fully complies with international standard BS EN818-7 Grade T (8).

PROOF TESTED: every hoist is proof tested to 1.5 times the Working Load Limit.

OPTIONAL EQUIPMENT:
– Overload Limiter
– Top and bottom hook adaptors
– Travelling End Stop

... *Read more*

Marking: According to standard
Temperature range: -20°C to +120°C
Standard: EN 13157

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lever Hoist WH L4

Blueprint



Technical data

Part Code	WLL ton	Lifting height m	Number of falls	a mm	b mm	c mm	d mm	e mm	h mm	Weight
500500030151000	0.25	1.5	1	-	-	-	-	-	-	1.6
500500050301000	0.5	3	1	148	121	41.5	265	28	280	4.7
500500050151000	0.5	1.5	1	148	121	41.5	265	28	280	6.2
500500050151004	0.5	1.5	1	148	121	41.5	265	28	280	6.2
500500080151004	0.8	1.5	1	148	121	41.5	265	28	280	6.2
500500160151004	1.6	1.5	1	165.5	141	52	350	33	350	9.6
500500320151004	3.2	1.5	1	194.5	178	61.9	415	42.5	420	15.5

© November 2026 - All Rights Reserved