Lifting Solutions Group
Axel Johnson International

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Product information

The Chain Sling Powertex 4-leg MC-4 with safety hooks is a four-leg lifting assembly for general industrial use. It features an MC-4 master link with integrated shortening functions on all 4 legs, reducing the number of components and creating a more compact and manageable lifting setup.

It is designed for balanced lifting where load distribution, individual leg adjustment, and predictable performance are required.

The assembly includes the MC-4 Master Link, Grade 10 chain, safety hooks, and a marking plate with WLL information, providing a complete, ready-to-use configuration.

Best used for:

- Lifting loads requiring multiple lifting points for stability
- Applications where a compact setup with integrated shortening is preferred
- Lifting applications where secure hook closure is required to reduce the risk of unintentional release

Product Benefits

- MC-4 master link integrates the shortening function, reducing the number of components and simplifying assembly configuration
- Individual leg shortening allows accurate load balancing without adding separate shortening hooks
- Compact design supports a clearer overview during use and inspection, helping reduce handling errors
- Safety hooks provide secure closure, helping reduce the chance of unintentional hook release during lifting
- Grade 10 chain provides higher capacity compared to Grade 8, enabling compact setups without increasing chain diameter

... *Read more*

Material: Alloy steel
Marking: According to standard, CE-marked
Temperature range: -40°C up to +200°C without reduction in WLL
Finish: Red powder paint
Standard: EN 818-4, AS 3776
(+25 % WLL)

Safety factor: 4:1
Grade: 10

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Technical data

Part Code	Chain size mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t
241300600100310	6	3	1	3	2.12
241300600200310	6	3	2	3	2.12
241300600300310	6	3	3	3	2.12
241300600400310	6	3	4	3	2.12
241300600500310	6	3	5	3	2.12
241300600600310	6	3	6	3	2.12
241300600700310	6	3	7	3	2.12
241300600800310	6	3	8	3	2.12
241300800100310	8	5.3	1	5.3	3.75
241300800200310	8	5.3	2	5.3	3.75
241300800300310	8	5.3	3	5.3	3.75
241300800400310	8	5.3	4	5.3	3.75
241300800500310	8	5.3	5	5.3	3.75
241300800600310	8	5.3	6	5.3	3.75
241300800700310	8	5.3	7	5.3	3.75
241300800800310	8	5.3	8	5.3	3.75
241301000100310	10	8.4	1	8.4	6
241301000200310	10	8.4	2	8.4	6
241301000300310	10	8.4	3	8.4	6
241301000400310	10	8.4	4	8.4	6
241301000500310	10	8.4	5	8.4	6
241301000600310	10	8.4	6	8.4	6
241301000700310	10	8.4	7	8.4	6
241301000800310	10	8.4	8	8.4	6
241301300200310	13	14	2	14	10
241301300300310	13	14	3	14	10
241301300400310	13	14	4	14	10
241301300500310	13	14	5	14	10
241301300600310	13	14	6	14	10
241301300700310	13	14	7	14	10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Sling Powertex 4-leg with Masterlink MC4 and Safety Hooks, Grade 10

Technical data

Part Code	Chain size mm	WLL ton	EWL m	WLL 0-45° t	WLL 45-60° t
241301300800310	13	14	8	14	10
241301600200310	16	21.2	2	21.2	15
241301600300310	16	21.2	3	21.2	15
241301600400310	16	21.2	4	21.2	15
241301600500310	16	21.2	5	21.2	15
241301600600310	16	21.2	6	21.2	15
241301600700310	16	21.2	7	21.2	15
241301600800310	16	21.2	8	21.2	15

Certex Lifting
info@certexlifting.com.au
1800 237 839

© November 2026 - All Rights Reserved